

Wastewater Treatment by Vermifiltration: A Review

Patel Jatin B.

M.E. Environmental Management, L.D. College of Engineering Ahmedabad, Gujarat, India

Abstract: A centralized treatment facility often faces problems of high cost of collection, treatment and disposal of wastewater and hence the growing needs for small scale decentralized eco-friendly alternative treatment options are necessary. Vermifiltration is such method where wastewater is treated using earthworms. Earthworm's body works as a biofilter and have been found to remove BOD, COD, TDS, and TSS by general mechanism of ingestion, biodegradation, and absorption through body walls. There is no sludge formation in vermifiltration process which requires additional cost on landfill disposal and it is also odor-free process. The present study will evaluate the performance of vermifiltration for parameters like Turbidity, BOD, COD, TDS, and TSS for industrial wastewater.

Keywords: Vermifiltration, Earthworms, Wastewater, Ingestion, Absorption

I. INTRODUCTION

The wastewater generation and its treatment has become a consequential health issue in the developing countries due to the inadequate treatment facilities. The discharge of untreated wastewater in surface and sub-surface water courses is the most important source of contamination of water resources. Most of the population living in rural and urban areas of developing nations depends upon onsite systems for the treatment of domestic wastewater. The treatment systems that require comparatively low costs, energy, and maintenance are better for the treatment of rural domestic wastewater. [25, 26]

Many solutions have been adopted for the treatment of domestic wastewater especially in rural areas, including constructed wetlands, soil infiltration trenches, vegetation-based wastewater treatment and vermifiltration [4, 9, 12, 31]. Among these technologies, the vermifiltration has represented its effectiveness as other technologies are restricted to ample occupying area. [15]

Vermifiltration of wastewater using earthworms is a newly conceived technology. Earthworm's body works as a 'biofilter' and they have been found to remove the 5 days' BOD (BOD₅), COD, total dissolved solids (TDS), and the total suspended solids (TSS) from wastewater by the general mechanism of 'ingestion' and biodegradation of organic wastes, heavy metals, and solids from wastewater and also by their 'absorption' through body walls. In vermifilter, the earthworms propel and facilitate up the microbial activity by increasing the population of soil microorganisms. [31]

Vermifiltration needs no external energy, except pumping. Because of this it can be very useful for small communities,

colonies and villages. Vermifiltration is more dependable than various other wastewater treatment technologies like constructed wet land, stabilization pond and other common technologies because these technologies need more area as compared to vermifiltration. [35] It has further been reported that vermifiltration process has equal efficiency to the activated sludge process. [18]

There is no sludge formation in the process which requires additional expenditure on landfill disposal. This is furthermore an odor-free process and the resulting vermifiltered water is clean enough to be reused in parks and gardens and for farm irrigation.

II. VERMIFILTRATION SYSTEM

Earthworms

The earthworms have around 600 million years of experience in waste and environmental management. Charles Darwin called them as the 'unheralded soldiers of mankind,' and the Greek philosopher Aristotle called them as the 'intestine of earth,' meaning digesting a wide variety of organic materials including the waste organics, from earth. [5,22]

Earthworms are long, cylindrical, narrow, bilaterally symmetrical, segmented animals without bones. The body is dark brown, glistening, and covered by all of delicate cuticle. They weigh around 1,400–1,500 mg after 8–10 weeks. On an average, 2,000 adult worms weigh 1 kg and one million worms weigh approximately 1 ton. Usually the life span of an earthworm is practically 3–7 years depending upon the type of species and the ecological situation. Earthworms nourish millions of 'nitrogen-fixing' and 'decomposer microbes' in their gut. They have 'chemoreceptors' which help in search of food.

The distribution of earthworms in soil depends on factors like availability of organic matter, soil moisture and pH of the soil. They develop in different habitats especially those which are dark and moist.

As worms breathe through their skin significant ventilation of air in soil medium is necessary. They can tolerate a temperature range between 5 and 29°C. A temperature of 20–25°C and moisture of 60–75% are optimum for good worm function. [10]

Earthworms are bisexual animals and multiply literally rapidly. Given the optimal conditions of temperature, moisture, and feeding materials earthworms can multiply by

28, i.e. 256 worms every 6 months from a single individual. The total life cycle of the worms is closely around 220 days. They produce 300–400 young ones within this life period. [10]

Earthworms are very sensitive to light, touch, and dryness. Low temperature is not a big problem for them as the high temperature. Their movement is significantly slowed down in winter, but heat can kill them instantly.

Table 1 Niche Diversification in Earthworms

Earthworm species	Weight adult worm(g)	Temperature tolerance (°c)	Moisture tolerance (%)	Active phase	Distribution
Eudrilus eugeniae	1.5-2.5	18-35	20-40	Throughout the year	Tropical Africa and south America
Eisenia fetida	0.3-0.7	15-30	20-40	Throughout the year	Temperate regions of Europe, north America, India
Perionyx excavatus	0.8-1.2	8-30	30-50	Throughout the year	Tropical countries
Dichogaster bolau	0.04-0.07	20-28	20-30	July- October	Tropical countries
Dicogaster affinis	0.04-0.07	20-28	20-30	July- October	Tropical countries
Drawida barwelli	0.2-0.5	20-30	40-50	August-November	Tropical countries shade essential for establishment
Lampito mauritii	0.8-1.5	18-28	20-40	June-august	Plains of Indian penninsula

Table 2 The Use of Vermifilter for Treatment of Various Wastewater

Sr. No.	Types of wastewater	Earthworm species	Organics removal (%)	Nutrient removal (%)	Bed material and size	HLR (m ³ /m ² d)	HRT (hour)
1	Sewage	Eisenia fetida	BOD 98, COD 45, TSS 90	-	pure soil, sand(10-12mm), gravel(7.5, of 3.5-4.5)	-	1-2
2	Dairy industry effluent	Earthworm	BOD 98, COD 80-90, TSS 90-95 TDS 90-92	-	pure soil, sand(10-12mm), gravel(7.5, of 3.5-4.5)	-	6-10
3	Synthetic sewage	Eisenia fetida	COD 83.6	TN 63, TP 86.7, NH ₃ -N 70.5	Cobblestones (6-10 cm), soil, sawdust	0.2	48,72,96
4	Urban wastewater	perionyx sansibaricus	COD 80-90, TSS 88.6, TDS 99.8	No ₃ 92.7, Po ₄ 98.3	surface vegetation, soil, dried leaves, sawdust, small stones (5-7cm), : large stones (10-15 cm)	-	1
5	Cheese way	Eisenia fetida	BOD 76, COD 82, TSS 77	TN 60, TP 77	Ligneous mature compost, stones	0.04	-
6	Sewage	Eisenia fetida	BOD 98, COD 70, TDS 95	-	garden soil, sand, aggregates (3-5,7-8 cm)	-	2
7	Rural domestic sewage	Eisenia fetida	BOD 78, COD 67.6, TSS 89.8	NH ₄ ⁺ 92.1	Ceramsite (3-5 mm)	4.2	-
8	Synthetic wastewater	Eisenia fetida	BOD 96, COD 90, TDS 82	-	Vermicompost, riverbed material (6-8 mm), sand (1-2mm), gravels (10-12.5mm)	1.5,2,2.5,3	-
9	Urban wastewater	Eisenia fetida	BOD 98.5, COD 74.3, TSS 96.6	NH ₄ ⁺ 99.1	Vermicompost, quartz sand, gravel (40mm)	2.6,1.3,0.8,0.6	2,4,6,8
10	Synthetic wastewater	Eisenia fetida	BOD 70-81, COD 59-72, TSS 55-75	-	Vermicompost, sand (2-4mm), riverbed material, wood coal, glass balls, mud balls, gravel (10-12.5mm)	1.5	-

III. REMOVAL OF BOD AND COD

BOD means the amount of dissolved oxygen that is required by aerobic bacteria to breakdown organic pollutants in wastewater. Earthworms significantly degrade the wastewater organics by enzymatic actions whereby the earthworms worked as biological catalysts resulting in faster biochemical reactions hence high BOD removal in the vermifilter. These indicate the major difference between vermi-degradation and microbial degradation.

COD means the chemical decomposition of organic and inorganic pollutants in wastewater which cannot be biologically removed. COD removed by earthworms was not as significant as the BOD removed; nevertheless, the COD amount removed was still practically higher than that removed by the microbial system. This was apparently because the enzymes in the gut of earthworms helped in the degradation of many of those chemicals which could not be decomposed by microbes.

Sinha et al. found the BOD and COD removal efficiency of 98% and 45%, respectively for sewage. Manyuchi et al. reported the use of vermifilter to treat sewage wastewater and the removal efficiency of BOD and COD were 98% and 70%, respectively. Tomar et al. also reported that a vermifilter removal efficiency of COD was 80-90% for urban wastewater. Xing et al. reported that a pilot scale vermifiltration removal efficiency for BOD and COD 54.7-66% and 47.3-64.7%, respectively. Ghatnekar et al. studied the efficiency of a pilot scale vermifilter to treat gelatine industry wastewater and its results suggested that vermifiltration decrease BOD and COD by 89% and 90%, respectively.

IV. REMOVAL OF TDSS

A total dissolved and suspended solid means the organic and inorganic pollutants which are either suspended or dissolved in the wastewater.

These solids which were trapped build up over time as sludge in a normal filter and choke the system which then ceases to function properly. However, in the vermifilter bed these bio-solids were consistently ingested by the earthworms and expelled as vermicompost. Therefore there was no choking and discontinuous functioning of the vermifilter bed.

Sinha et al. found the TSS and TDS removal efficiency of 90-95% and 90-92%, respectively for dairy industry wastewater. Manyuchi et al. reported the use of vermifilter to treat sewage wastewater and the removal efficiency of TDSS by 95%. Tomar et al. also reported that a vermifilter removal efficiency of TSS and TDS were 88.6% and 99.8% for urban wastewater. Xing et al. reported that pilot scale vermifiltration removal efficiency for TSS was 57-77.9%. Kumar et al. studied the efficiency of vermifilter to treat sewage

wastewater and its results suggested that vermifiltration decrease TDS by 82%.

V. REMOVAL OF NITROGEN AND PHOSPHORUS

Nitrate is a significant indicator of water pollution and its high concentration in freshwater bodies accelerate eutrophication problem. There are further plenty of nitrifying and denitrifying microbes present in the intestinal gut of earthworms. Due to burrowing movement of earthworms, atmospheric oxygen diffused into vermibed which enhance the nitrification process and supports creating a microenvironment for growth of aerobic nitrobacteria. Also worm casts aerate the influent and this aeration accelerates the nitrification of ammonia.

Merlin et al. reported 60% TN removal in a vermifilter for treatment of cheese whey effluent. Wang et al. reported 70.5% $\text{NH}_3\text{-N}$ and 63% TN removal for synthetic sewage treatment in vermifilter. Tomar et al. treated urban wastewater in a vermifilter and it remove 92.7% NO_3^- . Liu et al. confirmed maximum 92.1% $\text{NH}_4^+\text{-N}$ removal in 180 days experimentation while treating rural domestic sewage. Bajsa et al. has reported that earthworms secrete polysaccharides, proteins, and other nitrogenous compounds, and mineralize the nitrogen available in wastewater to make it available to the plants as nutrients.

Phosphorous removal completely depends on vermifilter bed material sorption capability, surface area and size. Besides that, chemical reaction like ligand exchange reaction, complexation and precipitation play a important role. The activities of earthworms and associated microbes in vermifilter bed encourage rapid phosphate mineralization in the system generating increased concentration of TP in the effluent.

Wang et al. reported 86.7% removal of TP from synthetic sewage in vermifilter. Tomar et al. treated urban wastewater in a vermifilter and it remove 98.3% PO_4^{3-} . Merlin et al. reported 77% TP removal in a vermifilter for treatment of cheese whey effluent. Li et al. obtained 62% TP removal using vermifilter for swine wastewater.

VI. ADVANTAGES OF VERMIFILTRATION

- i. Vermifiltration treatment is low energy dependent and has distinct advantage over all the conventional biological wastewater treatment systems- the Activated Sludge Process, Trickling Filters, and Rotating Biological Contactors which are highly energy intensive, costly to install and operate, and do not generate any income.
- ii. In the vermifilter process there is 100% capture of organic materials, the capital and operating costs are less, and there is high value added end product (vermicompost).

- iii. sludge is discharged in the vermifilter bed as excreta (vermicompost) which is useful soil additive for agriculture and horticulture
- iv. There is no foul odor as the earthworms arrest rotting and decay of all putrescible matters in the wastewater and the sludge.
- v. Large quantities of worm biomass will be available as food for the cattle, poultry, and fish farming, after the first year of vermitreatment.
- vi. It can utilize waste organics that otherwise cannot be utilized by other technologies.
- vii. Achieve greater utilization of waste materials that cannot be achieved by other technologies.

VII. CONCLUSION

This paper describes the basic mechanism of vermifilter and vermifilter was found to be suitable technique for highly efficient treatment technology for wastewater. This is also a good alternative treatment for decentralized onsite treatment. Earthworms are protective and productive organisms and they play a significant role in breaking pollutants and aerating filter bed. Vermifiltration process driven by the earthworms likely to become more vigorous and efficient with time as the army of worms grows. It further keeps the system thoroughly aerated with plenty of oxygen available for aerobic decomposer microbes. The treated effluent had higher value of nitrate and phosphate concentration which is best suited for sewage farming or horticulture. No sludge was produced and the organic matter and solids present in the wastewater were consumed by earthworms transforming these into valuable vermicompost. This vermicompost can be used as manure as it is having good content of nitrogen and phosphate. Still there are some limitation of vermifilter like vermifilter cleaning process, heavy metals removal, wastewater feeding mode, and saline water treatment. Hence in order to make vermifilter efficient and sustainable more research related to optimum wastewater feeding mode, cleaning mechanism, integration with other technologies and other more efficient earthworm species is required.

REFERENCES

- [1]. Azuar S. A. and Ibrahim M. H., "Comparison of sand and oil palm fibre vermibeds infiltration of palm oil mill effluent (POME)", UMT 11th International Annual Symposium on Sustainability Science and Management (09th -11th July 2012), Terengganu, Malaysia, pp. 1414-1419.
- [2]. Bajsa O., Nair J., Mathew K. and Ho G. E., "Vermiculture as a tool for domestic wastewater management." *Water Sci. Technol.* (2003), vol. 48 (11-12), pp. 125-132.
- [3]. Brown G.G., Barois I. and Lavelle P., "Regulation of soil organic matter dynamics and microbial activity in the drilosphere and the role of interactions with other edaphic functional domains." *Eur. J. Soil Biol.* (2000), vol. 36, pp. 177-198.
- [4]. Cuyk S.V., Siegrist R., Logan A., Masson S., Fischer E., Figueroa L., "Hydraulic and purification behaviors and their interactions during wastewater treatment in soil infiltration systems." *Water Res.* (2001), vol. 43, pp. 297-305.
- [5]. Darwin F and Seward AC, "More letters of Charles Darwin. A record of his work in series of hitherto unpublished letters." John Murray, London, (1903), vol. 2, pp. 508.
- [6]. Dhadse S., Satyanarayan S., Chaudhari P. and Wate S., "Vermifilters: a tool for aerobic biological treatment of herbal pharmaceutical wastewater." *Water Sci. Technol.* (2010), vol. 61, pp. 2375-2380.
- [7]. Ghatnekar S. D., Kaviani M. F., Sharma S. M., Ghatnekar S. S., Ghatnekar G. S. and Ghatnekar A. V., "Application of vermifilter-based effluent treatments from the gelatine industry." *Dynamic Soil, Dynamic Plant* (2010), pp. 83-88.
- [8]. Gomez-Brandon M., Aira M., Lores M. and Domínguez J., "Changes in microbial community structure and function during vermicomposting of pig slurry." *Bioresour. Technol.* (2011), vol. 102, pp. 4171-4178.
- [9]. Ham J.H., Yoon C.G., Jeon J.H., Kim H.C., "Feasibility of a constructed wetland and wastewater stabilisation pond system as a sewage reclamation system for agricultural reuse in a decentralised rural area." *Water Sci. Technol.* (2007), vol. 55, pp. 503-511.
- [10]. Hand P., "Earthworm biotechnology." In: Greenshields R (ed) *Resources and application of biotechnology: the new wave.* MacMillan Press Ltd, US (1988).
- [11]. Jiang L., Liu Y., Hu X., Zeng G., Wang H., Zhou L., Tan X., Huang B., Liu S. and Liu S., "The use of microbial-earthworm ecofilters for wastewater treatment with special attention to influencing factors in performance: a review." *Biores. Technol.* (2016), vol. 200, pp. 999-1007.
- [12]. Kaoru A., Kunihiko K., Yasuo O., "Vegetation-based wastewater treatment technologies for rural areas in Japan." *JARQ* (2010), vol. 44, pp. 231-242.
- [13]. Kharwade M. and Khedikar I. P., "Laboratory scale studies on domestic grey water through vermifilter and non-vermifilter." *Journal of Engineering Research and Studies* (2011), vol. 2 (4), pp. 35-39.
- [14]. Kumar Tarun, Bhargava Renu, Hari Prasad K.S. and Pruthi Vikas, "Evaluation of vermifiltration process using natural ingredients for effective wastewater treatment." *Ecological Engineering* (2015), vol. 75, pp. 370-377.
- [15]. Kumar Tarun, Rajpal Ankur, Bhargava Renu and Hari Prasad K.S., "Performance evaluation of vermifilter at different hydraulic loading rate using river bed material." *Ecological Engineering* (2014), vol. 62, pp. 77-82.
- [16]. Liu J., Lu Z., Zhang J., Xing M., Yang J., "Phylogenetic characterization of microbial communities in a full-scale vermifilter treating rural domestic sewage." *Ecol. Eng.* (2013), vol. 61, pp. 100-109.
- [17]. Li Y. S., Robin P., Cluzeau D., Bouche M., Qiu J. P., Laplanche A., Hassouna M., Morand P., Dappelo C. and Callarec J., "Vermifiltration as a stage in reuse of swine wastewater: monitoring methodology on an experimental farm." *Ecol. Eng.* (2008), vol. 32, pp. 301-309.
- [18]. Li Y.S., Xiao Y.Q., Qiu J.P., Dai Y.Q., Robin Paul., "Continuous village sewage treatment by vermifiltration and activated sludge process." *Water Sci. Technol.* (2009), vol. 60, pp. 3001-3010.
- [19]. Lourenco N. and Nunes L. M., "Optimization of a vermifiltration process for treating urban wastewater." *Ecological Engineering* (2017), vol. 100, pp. 138-146.
- [20]. Martin JP., "Darwin on earthworms: the formation of vegetable moulds." Bookworm Publishing, ISBN (1976) 0-916302-06-7.
- [21]. Merlin G. and Cottin N., "Performance of a compost biofilter containing earthworms to treat cheese whey." *Environ. Technol.* (2009), vol. 30 (10), pp. 995-1002.
- [22]. Samal Kundan, Dash Roshan Rajesh and Bhunia Puspendu, "Treatment of wastewater by vermifiltration integrated with macrophyte filter: A review." *Journal of Environmental Chemical*

- Engineering (2017), vol. 5, pp. 2274-2289.
- [23]. Sharma M.K., Kazmi A.A., "Effect of physical property of supporting media and variable hydraulic loading on hydraulic characteristics of advanced onsite wastewater treatment system." *Env Technol.*(2014) doi:<http://dx.doi.org/10.1080/09593330.2014.992480>.
- [24]. Sharma M.K., khursheed A., Kazmi A.A., "Modified septic tank anaerobic filter unit as a two-stage onsite domestic wastewater treatment system." *Env. Technol.* (2014), vol. 35, pp. 2183–2193.
- [25]. Singh N.K., Kazmi A.A., Starkl M., "A review on full-scale decentralized wastewater treatment systems: techno-economical approach." *Water Sci. Technol.* (2014) doi:<http://dx.doi.org/10.2166/wst.2014.413>.
- [26]. Sinha R. K., Agarwal S., Chauhan K., Chandran V. and Soni B. K., "Vermiculture technology: Reviving the dreams of Sir Charles Darwin for Scientific Use of Earthworms in Sustainable Development Programs." *Technology and Investment* (2010), vol. 1, pp. 155-172.
- [27]. Sinha R. K., Bharambe G. and Bapat P., "Removal of high BOD and COD loadings of primary liquid waste products from dairy industry by vermi-filtration technology using earthworms." *IJEP* (2007), vol. 27 (6), pp. 486-501.
- [28]. Sinha R. K., Chauhan K., Valan D., Chandran V., Soni B. K. and Patel V., "Earthworms: Charles Darwin's unheralded soldiers of mankind: Protective and Productive for Man and Environment." *Journal of Environmental Protection* (2010), vol. 1, pp. 251-260.
- [29]. Sinha Rajiv K., Bharambe Gokul and Chaudhari Uday, "Sewage treatment by vermifiltration with synchronous treatment of sludge by earthworms: a low-cost sustainable technology over conventional systems with potential for decentralization." *Environmentalist* (2008), vol. 28, pp. 409-420.
- [30]. Tomar Priyanka and Suthar Surindra, "Urban wastewater treatment using vermi-biofiltration system." *Desalination* (2011), vol. 282, pp. 95-103.
- [31]. Trivedi R. K. and Kumar Arvind, "Ecotechnology for pollution control and environmental management" *Enviro Media* (1998).
- [32]. Wang L., Guo Z., Che Y., Yang F., Chao J., Gao Y. and Zhang Y., "The effect of vermifiltration height and wet: dry time ratio on nutrient removal performance and biological features: and their influence on nutrient removal efficiencies." *Ecol. Eng.* (2014), vol. 71, pp. 165–172.
- [33]. Xing M., Li X. and Yang J., "Treatment performance of small-scale vermifilter for domestic wastewater and its relationship to earthworm growth, reproduction and enzymatic activity." *African Journal of Biotechnology* (2010), vol. 9 (44), pp. 7513-7520.